



900xl

Stereo Power Amplifier (10 Watts per Channel)

| Speakers



The 900xl is a high-performance power amplifier for line level stereo audio signals. The unit accepts unbalanced audio signals on either of two RCA or 3.5mm connectors and delivers a speaker output of 10 watts RMS per channel into a 4Ω load

FEATURES

High Efficiency - Class D operation

S/N Ratio - 60dB

Control - Volume & input selection from front panel & RS-232

Compact Kramer TOOLS™ - 3 units can be rack mounted side-by-side in a 1U rack space with the recommended rack adapter



KRAMER

TECHNICAL SPECIFICATIONS

| | |
|------------------------|---|
| INPUTS: | 1 unbalanced stereo audio on a 3.5mm mini jack connector, 1 unbalanced stereo audio on RCA connectors |
| OUTPUT: | 1 stereo differential speaker output |
| OUTPUT POWER: | 2x10W (4Ω) |
| INPUT SENSITIVITY: | 460mV |
| OUTPUT MUSIC POWER: | 2x40W (4Ω) |
| BANDWIDTH (-3dB): | 25kHz |
| S/N RATIO: | 85dB @1kHz, 0dBu output |
| CONTROLS: | Gain range: -14 to +32dB at high-gain; -21 to +20dB at low-gain |
| COUPLING: | Input: AC; output: DC |
| AUDIO THD + NOISE: | 0.6% @0dBu output |
| AUDIO 2nd HARMONIC: | 0.35% @0dBu output |
| POWER CONSUMPTION: | 12V DC, 2.0A |
| OPERATING TEMPERATURE: | 0° to +40°C (32° to 104°F) |
| STORAGE TEMPERATURE: | -45° to +72°C (-49° to 162°F) |
| HUMIDITY: | 10% to 90%, RHL non-condensing |
| INCLUDED ACCESSORIES: | Power supply |
| Product Dimensions | 12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H |
| Product Weight | 0.0kg (0.0lbs) approx |
| Shipping Dimensions | 15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H |
| Shipping Weight | 0.6kg (1.4lbs) approx |

