

907xl

Stereo Power Amplifier/Mixer (40 Watts per Channel)

| Speakers



The 907xl is a high-performance power amplifier for line-level stereo audio signals. It accepts a balanced stereo audio signal on a terminal block connector and an unbalanced stereo signal on RCA connectors. It delivers 40 watts per channel into an 8Ω load

FEATURES

High Efficiency - Class D operation Controls - 1 volume control knob for each input & mute button Gain Control DIP-Switches Mute and On Indicator LEDs Compact MultiTOOLS® - Up to 4 units can be rack mounted side-by-side in a 1U rack space with the recommended rack adapter



TECHNICAL SPECIFICATIONS

INPUTS:	1 balanced stereo audio on a terminal block connector, 1 unbalanced stereo audio on RCA connectors
OUTPUT:	Speaker output on a terminal block connector
OUTPUT POWER:	40W per channel into 8Ω
OUTPUT MUSIC POWER:	150W per channel into 8 Ω
INPUT SENSITIVITY:	1.2Vrms
AMPLIFIER TYPE:	Class D
VOLTAGE GAIN:	36dB (x10)
BANDWIDTH (-3dB):	25kHz
S/N RATIO:	66dB
COUPLING:	Inputs: AC, Outputs: DC
AUDIO THD + NOISE:	1.2%
AUDIO 2nd HARMONIC:	1%
POWER CONSUMPTION:	24V DC, 2.2A
CONTROLS:	2 gain DIP-switches, mute button, 2 input level knobs, 1 volume knob
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
INCLUDED ACCESSORIES:	Power supply
Product Dimensions	10.68cm x 10.35cm x 4.36cm (4.20" x 4.07" x 1.72") W, D, H
Product Weight	0.4kg (0.8lbs) approx
Shipping Dimensions	35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83") W, D, H
Shipping Weight	1.3kg (2.9lbs) approx

