



DS110SP

LINE SYSTEM SERIES PASSIVE SPEAKER FOR LOW FREQUENCIES



Overview

Engineered and designed to complete the low-frequency response of the DS112PT, the DP110SP is small in size and structure to allow integration into any type ceiling, wall or roofs for both indoor and outdoor installations. The DS110SP features 1 x high excursion 10" woofer. The housing of the DS110SP is made of steel, which has been treated and painted to provide the unit with high resistance against atmospheric agents over time. Degree of protection IP 55 Δ.



Technical Specifications

- Model: DS110T
- System: SUB
- Input power rating (continuous): 400W (8Ω)
- Input power rating (peak): 800W (8Ω)
- Nominal Impedance: 4Ω
- Frequency response: 30 Hz - 250 Hz
- Maximum (peak) Output: 127dB @ 1m
- Low Frequency Device: 10" woofer
- Angular coverage: omni

- Mounting Pole: custom arm or flange (wall / ceiling)
- Connectors: 2 pole cable
- Material: Steel Box (z/c treatment)
- Finish: P/E Scratch-proof coating
- Color Custom: (RAL code)
- Weight: - kg
- Dimensions: Ø510 x H208 mm
- Protection rating: IP55 Δ

Related Products



DS112P

Technical specifications and appearances are subject to change without notice and accuracy is not guaranteed. All trademarks are the property of their respective owners. PROEL accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colors and specifications may vary from actual product. PROEL products are sold through authorized fullfillers and resellers only. This manual is copyrighter. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of PROEL - Via alla Ruenia 37/43 - CAP 64027 - Sant'Omero (TE) ITALY.

For service, support, or more information contact:

Proel S.p.A.

Via alla Ruenia 37/43

CAP 64027 - Sant'Omero (TE) ITALY

PROEL 