



kramer

Galil 8-C

8-Inch, 2-Way Closed-Back Ceiling
Speakers

| Speakers



The Galil 8-C Closed-back Ceiling Speaker features a multi-tap power transformer for selecting 8 Ω (bypassing the transformer) or 70V/100V power settings that are suitable for an array installation

FEATURES

Type - 2-way coaxial speaker

Woofer - 8" polypropylene cone

Tweeter - 1" silk dome

Impedance - 8 Ω

Power Handling - 64W RMS, 180W continuous program

Transformer Taps - 70V: 64W/32W/16W/8W/4W/Off (Lo-Z); 100V: 64W/32W/16W/8W/Off (Lo-Z)

UL 1480 & 2043 Listed

Package Includes - 2 speakers (1 pair), ceiling mounting kit, template and user manual



kramer

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------|---|
| DESCRIPTION: | 2-way closed-back ceiling speakers |
| FREQUENCY RESPONSE: | 65Hz to 20kHz @-10dB, 85Hz to 20kHz @±3dB |
| WOOFER: | 8" (200mm) polypropylene with rubber surround |
| TWEETER: | 1" (25.4mm) silk dome |
| IMPEDANCE: | 8Ω (transformer tap in off position) |
| TRANSFORMER TAPS: | 70V – 64W/32W/16W/8W/4W/Off (Lo-Z), 100V – 64W/32W/16W/8W/Off (Lo-Z) |
| SENSITIVITY: | 89dB SPL, 1W@1m |
| MAX SPL: | Continuous: 104dB, peak: 107dB |
| POWER HANDLING: | 64W RMS, 180W continuous program |
| CROSSOVER FREQUENCY: | 6.3kHz |
| COVERAGE ANGLE: | 110° |
| DIRECTIVITY FACTOR (Q): | 4.6 averaged 1kHz to 10kHz |
| DIRECTIVITY INDEX (DI): | 6.5dB averaged 1kHz to 10kHz |
| INPUT CONNECTOR: | Terminal block |
| MATERIALS: | ABS bezel, aluminum grill, metal back can |
| OPERATING TEMPERATURE: | 0° to +40°C (32° to 104°F) |
| STORAGE TEMPERATURE: | -40° to +70°C (-40° to 158°F) |
| HUMIDITY: | 10% to 90%, RHL non-condensing |
| WEIGHT PER SINGLE SPEAKER: | 4.9kg (10.8lbs) approx |
| SHIPPING WEIGHT (FOR PAIR): | 13.6kg (30lbs) approx |
| INSTALLATION CLEARANCE: | Mounting depth: 22.6cm (8.9") |
| CUTOUT DIAMETER | 27.3cm (10.75") |
| ACCESSORIES: | Installation bracket, safety cord attached to grill, ceiling mounting kit |
| COLOR: | White |

