



J2630 HD Color IP-Camera

Video System	1080p,720p
Sensor	1/2.8", Effective Pixel: 2.07M
Scanning Mode	Progressive
Lens	12x, f3.5mm ~ 42.3mm, F1.8 ~ F2.8
Minimal Illumination	0.5 Lux @ (F1.8, AGC ON)
Shutter	1/30s ~ 1/10000s
White Balance	Auto, 3000K/Indoor, 4000K, 5000K/Outdoor, 6500K_1, 6500K_2, 6500K_3, One Push, Manual
Backlight Compensation	Support
Digital Noise Reduction	2D&3D Digital Noise Reduction
Video S/N	≥55dB
Horizontal Angle of View	72.5° ~ 6.9°
Vertical Angle of View	44.8° ~ 3.9°
Ceiling Installation	Support
Number of Preset	128
IPC Video Features	
Video coding standard	H.264/H.26/MJPEG
Video Stream	Main stream, Sub stream
Main stream resolution	1920x1080, 1280x720, 1024x576
Sub stream resolution	720x576, 720x480, 320x240
Video Bit Rate	128Kbps ~ 20480Kbps
Bit Rate Type	Variable rate, fixed rate
Frame Rate	50Hz: 1fps ~ 50fps, 60Hz: 1fps ~ 60fps
Web Stream	AAC
Web video size	96Kbps, 128Kbps, 256Kbps
Support protocols	TCP/IP, HTTP, RTSP, RTMP, Onvif, DHCP, Multicast, etc.
Input/Output Interface	
HD Output	1xSDI: BNC Type, 800mVp-p, 75Ω, Conforming to SMPTE 292M
Control Input/Output	1xRS-485: 2pin, Max Distance: 1500m, Protocol: VISCA/Pelco-D/Pelco-P
Audio interface	1-ch 3.5mm audio interface, LINE IN/LINE OUT
Network interface	1xRJ45: 10M/100M Adaptive Ethernet ports
Power Connector	JEITA type (DC IN 12V)
Generic Specification	
Input Voltage	DC 12V
Current Consumption	1.0A (Max)
Operating Temperature	-40°C ~ 60°C
Storage Temperature	-20°C ~ 60°C
Power Consumption	≤3.5W
Dimensions	138.5mm x 76.8mm x 60.3mm
mean time between failures	30000h
Weight	1.2Kg