



KRAMER

OSP-SM10S

Optical SFP+ Transceiver Pair over 10G
1270/1330nm Simplex SM Fiber



OSP-SM10S is a pair of fiber optic transceivers for 1270/1330nm single-mode signals. These standard pluggable SFP+ optical modules have one LC connector for reception and transmission of signals over one strand of single-mode optical fiber

FEATURES

Certified Transceiver - Kramer certified, hot-pluggable, simplex SFP+ optical modules, for high-quality transmission of 10.2Gbps signal over single-mode fiber cable, connecting 1 single-mode fiber strand via LC PC/UPC connector



TECHNICAL SPECIFICATIONS

General	<p>Optical Line: Single-mode G.652D compliant OFNR fiber</p> <p>Nominal Peak Wavelength: Module A: 1270 transmitter /1330nm receiver</p> <p>Module B: 1330 transmitter /1270nm receiver</p> <p>Max. Data Rate: 10.2Gbps</p> <p>Transmitter Type: DFB</p> <p>Optical Typical Transmission Power: -5dBm</p> <p>Optical Typical Maximum Receiver Sensitivity: -14dBm</p> <p>Optical Typical Maximum Loss Budget: 9dB</p>
Ports	<p>1 Optical: On single-strand LC-connected single-mode fiber</p> <p>Note: Do not use with LC(APC) cable connectors</p>
Extension Line	<p>Max. Reach: 20Km (12.4 miles) reach over OS1 SM fiber</p>
Regulatory Compliance (Standards Compliance)	<p>Quality: IEEE 802.3ae, SFF-8431, SFF-8472</p> <p>Laser Safety: Laser Class I</p> <p>Safety: FDA CDRH 1040.10, TUV EN60950-1 and EN60825-1/2, UL and CSA EN60950-1, RoHS, EMC EN 55032 and EN 55024</p>
Power	<p>Consumption: 1W</p>
Environmental Conditions	<p>Operating Temperature: 0° to 70°C</p> <p>Storage Temperature: -40° to 85°C</p> <p>Humidity: 5% to 95% RH</p>
Product Dimensions	<p>1.33cm x 5.70cm x 0.85cm (0.52" x 2.24" x 0.33") W, D, H</p>
Product Weight	<p>0.1kg (0.1lbs) approx</p>
Shipping Dimensions	<p>12.60cm x 8.40cm x 4.10cm (4.96" x 3.31" x 1.61") W, D, H</p>
Shipping Weight	<p>0.1kg (0.2lbs) approx</p>