

PMW 7014 Medical wall mount

Article number (SKU) Colour

7370141 White


Key Benefits

- Anti-sceptic powder coating
- Ergonomic
- Gas spring supported arm
- Internal cable management

With this medical mount you will be able to mount a display to the wall in order to give the patient the best possible AV experience.

This wall mount has 4 pivot points and is suitable for screens up to 29" (74 cm). The weight capacity of the product is 1-4 kg. This wall mount is suitable for screens that meet VESA hole patterns of 75x75 or 100x100 mm. Tablets can be installed by using our attractive TabLock enclosures. The antiseptic powder coating assist in controlling the spread of diseases.









PMW 7014 Medical wall mount



VOGEL'S HOLDING BV 2019 (c) All rights reserved Subject to printing errors, technical and price amendments Date:2019-05-16

www.vogels.com

Specifications

Article number (SKU)7370141ColourWhiteEAN single box8712285334788TÜV certifiedYesTiltTilt up to 90°TurnUp to 360°Guarantee2 yearsMax. weight load (kg)4Max. bolt sizeM4Max. height of interface (mm)160Max. width of interface (mm)150Cable managementCable managementMax. distance to the wall (mm)1750Max. screen size (inch)29Max. vertical hole pattern (mm)575Min. horizontal hole pattern575Min. horizontal hole pattern75Min. vertical hole pattern (mm)75Min. vertical h	Product type number	PMW 7014
EAN single box 8712285334788 TÜV certified Yes Tilt Tilt up to 90° Turn Up to 360° Guarantee 2 years Max. weight load (kg) 4 Max. bolt size M4 Max. height of interface (mm) 160 Max. width of interface (mm) 150 Cable management Cable management Max. distance to the wall (mm) 1750 Max. horizontal hole pattern 100 Max. vertical hole pattern (mm) 575 Min. horizontal hole pattern 75 Min. vertical hole pattern (mm) 75 Min. weight load (kg) 1 Number of pivot points 4	Article number (SKU)	7370141
TÜV certifiedYesTiltTilt up to 90°TurnUp to 360°Guarantee2 yearsMax.weight load (kg)4Max.bolt sizeM4Max.height of interface (mm)160Max.width of interface (mm)150Cable managementCable managementMax.distance to the wall (mm)1750Max.screen size (inch)29Max.vertical hole pattern100Max.vertical hole pattern575Min.horizontal hole pattern575Min.h	Colour	White
Tilt Tilt up to 90° Turn Up to 360° Guarantee 2 years Max.weight load (kg) 4 Max.bolt size M4 Max.height of interface (mm) 160 Max.width of interface (mm) 150 Cable management Cable management Max.distance to the wall (mm) 1750 Max.screen size (inch) 100 Max.vertical hole pattern 100 Min. distance to the wall (mm) 575 Max.vertical hole pattern 575 Min. horizontal hole pattern 575 Min. horizontal hole pattern 75 Min. vertical hole pattern (mm) 575 Min. weight load (kg) 1 Min.weight load (kg) 1 Min.weight load (kg) 1 Min.weight load (kg) 1 Mumber of pivot points 4	EAN single box	8712285334788
Turn Up to 360° Guarantee 2 years Max.weight load (kg) 4 Max.bolt size M4 Max.height of interface (mm) 160 Max.width of interface (mm) 150 Cable management Cable management Max.distance to the wall (mm) 1750 Max. horizontal hole pattern 100 (mm) 29 Max.vertical hole pattern (mm) 575 Min. horizontal hole pattern 75 Min. vertical hole pattern (mm) 75 Min. vertical hole pattern (mm) 75 Min. weight load (kg) 1 Number of pivot points 4	TÜV certified	Yes
Guarantee 2 years Max. weight load (kg) 4 Max. bolt size M4 Max. height of interface (mm) 160 Max. width of interface (mm) 150 Cable management Cable management Max. distance to the wall (mm) 1750 Max. horizontal hole pattern 100 (mm) 29 Max. vertical hole pattern (mm) 575 Min. horizontal hole pattern (mm) 575 Min. horizontal hole pattern (mm) 75 Min. weight load (kg) 1 Min. weight load (kg) 1 Number of pivot points 4	Tilt	Tilt up to 90°
Max.weight load (kg) 4 Max.bolt size M4 Max.height of interface (mm) 160 Max.width of interface (mm) 150 Cable management Cable management Max.distance to the wall (mm) 1750 Max.horizontal hole pattern 100 (mm) 29 Max.vertical hole pattern (mm) 575 Min.horizontal hole pattern 75 Min.horizontal hole pattern (mm) 75 Min.weight load (kg) 1 Number of pivot points 4	Turn	Up to 360°
Max. bolt sizeM4Max. height of interface (mm)160Max. width of interface (mm)150Cable managementCable managementMax. distance to the wall (mm)1750Max. horizontal hole pattern100(mm)29Max. vertical hole pattern (mm)100Min. distance to the wall (mm)575Min. horizontal hole pattern (mm)575Min. vertical hole pattern (mm)575M	Guarantee	2 years
Max. height of interface (mm) 160 Max. width of interface (mm) 150 Cable management Cable management Max. distance to the wall (mm) 1750 Max. horizontal hole pattern 100 (mm) 29 Max. vertical hole pattern (mm) 575 Min. horizontal hole pattern 75 Min. vertical hole pattern (mm) 75 Min. horizontal hole pattern (mm) 75 Min. weight load (kg) 1 Number of pivot points 4	Max. weight load (kg)	4
Max. width of interface (mm)150Cable managementCable managementMax. distance to the wall (mm)1750Max. horizontal hole pattern100(mm)29Max. vertical hole pattern (mm)100Min. distance to the wall (mm)575Min. horizontal hole pattern75Min. horizontal hole pattern (mm)75Min. vertical hole pattern (mm)100Min. horizontal hole pattern75Min. horizontal hole pattern (mm)4	Max. bolt size	M4
Cable managementCable management integrated in armMax. distance to the wall (mm)1750Max. horizontal hole pattern100(mm)29Max. vertical hole pattern (mm)100Min. distance to the wall (mm)575Min. horizontal hole pattern75Min. horizontal hole pattern (mm)75Min. vertical hole pattern (mm)100Min. vertical hole pattern100Min. horizontal hole pattern75Min. vertical hole pattern (mm)75Min. weight load (kg)1Number of pivot points4	Max. height of interface (mm)	160
Max. distance to the wall (mm)integrated in armMax. horizontal hole pattern1750Max. horizontal hole pattern100(mm)29Max. vertical hole pattern (mm)100Min. distance to the wall (mm)575Min. horizontal hole pattern75(mm)75Min. vertical hole pattern (mm)75Min. vertical hole pattern (mm)100Min. vertical hole pattern (mm)75Min. vertical hole pattern (mm)75Min. vertical hole pattern (mm)1Min. vertical hole pattern (mm)1Min. weight load (kg)1Number of pivot points4	Max. width of interface (mm)	150
Max. distance to the wall (mm)1750Max. horizontal hole pattern100(mm)29Max. screen size (inch)29Max. vertical hole pattern (mm)100Min. distance to the wall (mm)575Min. horizontal hole pattern75Min. vertical hole pattern (mm)75Min. vertical hole pattern (mm)10Min. vertical hole pattern (mm)4	Cable management	Cable management
Max. horizontal hole pattern100(mm)29Max. screen size (inch)29Max. vertical hole pattern (mm)100Min. distance to the wall (mm)575Min. horizontal hole pattern75(mm)75Min. vertical hole pattern (mm)75Min. weight load (kg)1Number of pivot points4		integrated in arm
(mm)Max. screen size (inch)29Max. vertical hole pattern (mm)100Min. distance to the wall (mm)575Min. horizontal hole pattern75(mm)75Min. vertical hole pattern (mm)75Min. weight load (kg)1Number of pivot points4	Max. distance to the wall (mm)	1750
Max. screen size (inch)29Max. vertical hole pattern (mm)100Min. distance to the wall (mm)575Min. horizontal hole pattern75(mm)75Min. vertical hole pattern (mm)75Min. weight load (kg)1Number of pivot points4	Max. horizontal hole pattern	100
Max. vertical hole pattern (mm)100Min. distance to the wall (mm)575Min. horizontal hole pattern75(mm)75Min. vertical hole pattern (mm)75Min. weight load (kg)1Number of pivot points4	(mm)	
Min. distance to the wall (mm)575Min. horizontal hole pattern75(mm)75Min. vertical hole pattern (mm)75Min. weight load (kg)1Number of pivot points4	Max. screen size (inch)	29
Min. horizontal hole pattern75(mm)75Min. vertical hole pattern (mm)75Min. weight load (kg)1Number of pivot points4	Max. vertical hole pattern (mm)	100
(mm)Min. vertical hole pattern (mm)75Min. weight load (kg)1Number of pivot points4	Min. distance to the wall (mm)	575
Min. vertical hole pattern (mm)75Min. weight load (kg)1Number of pivot points4	Min. horizontal hole pattern	75
Min. weight load (kg)1Number of pivot points4	(mm)	
Number of pivot points 4	Min. vertical hole pattern (mm)	75
	Min. weight load (kg)]
I Iniversal or fived hole pattern Eived	Number of pivot points	4
	Universal or fixed hole pattern	Fixed



