

PSE-1 Single 10G HDBaseT & Ethernet Power Injector

| HDBaseT



The PSE-1 provides power remotely over Ethernet to any device capable of acting as a PoE acceptor (for example, a wallplate, where it may be difficult to connect an external power supply). This allows a single HDBT LAN cable to provide both data and electrical power to compatible devices

FEATURES

Total Range - Up to 100m (328ft) @4K on shielded Kramer HDBaseT cable (or equivalent) 48V DC Power



TECHNICAL SPECIFICATIONS

INPUT/OUTPUT: 1 HDBaseT/LAN + PoE on an RJ-45 connector, 1 HDBaseT/LAN on an RJ-45

connector

OPERATION BANDWIDTH: Up to 10.2Gbps (3.4Gbps per data channel)

COMPLIANCE WITH

Supports HDMI, HDCP **HDMI STANDARD:**

INDICATOR LEDS: ON, PoE STATUS

POWER SOURCE: 48V DC, 630mA (device plus remote power sink)

POWER PROVISION: Up to 13W

OPERATING

0° to +40°C (32° to 104°F)

TEMPERATURE:

STORAGE -40° to +70°C (-40° to 158°F)

TEMPERATURE:

HUMIDITY: 10% to 90%, RHL non-condensing

COOLING: Convection, vents

ENCLOSURE TYPE: Aluminum

RACK MOUNT: With optional adapter

FURNITURE MOUNT: With included rubber feet

VIBRATION: ISTA 1A in carton (International Safe Transit Association)

SAFETY

CE, c-UL, UL

REGULATORY

COMPLIANCE:

CE, C-tick, FCC Class A, ICES, KCC, VCCI EMI/EMC

REGULATORY COMPLIANCE:

ENVIRONMENTAL REGULATORY COMPLIANCE:

Complies with appropriate requirements of RoHs and WEEE

INCLUDED

ACCESSORIES:

Power supply

WARRANTY: 7 years parts and labor

Product Dimensions 12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

Product Weight 0.2kg (0.4lbs) approx

Shipping Dimensions 49.00cm x 18.60cm x 58.80cm (19.29" x 7.32" x 23.15") W, D, H

Shipping Weight 0.7kg (1.5lbs) approx

