

RTBUS-25xl

Round Table Mount Multi-Connection Solution - Pneumatic Lid

| VGA/UXGA - 15-pin HD | HDMI | Ethernet - RJ-45



The RTBUS-25xI is an elegant furniture-mounted, modular, round connection bus featuring a pneumatic mechanism for pneumatic lifting and smooth closing of its lid. It is easily installed into a table or podium top and its interface enables you to connect any equipment to systems installed in a room via pass-through connectors for PC, USB, stereo audio, HDMI, Ethernet and power.

NOTE: The power socket and power cord are purchased separately

FEATURES

Inputs - 15-pin HD, USB, 3.5mm, HDMI, Ethernet

Cover - Pop-up pneumatic lid

Cutout Size (Mount Dimension) - 111-114mm diameter



TECHNICAL SPECIFICATIONS

Ports 1 HDMI: On a female HDMI connector

1 VGA: On a 15-pin d-sub connector

1 Audio: On a 3.5mm mini jack

1 Ethernet: On an RJ-45 connector

1 USB: On a female USB type-A connector

PHYSICAL Cutout Size 111-114mm diameter

Environmental Conditions

Operating Temperature: 0° to +40°C (32° to 104°F)

Storage Temperature: -40° to +70°C (-40° to 158°F)

Humidity: 10% to 90%, RHL non-condensing

Power Power rating varies according to the location and the power socket assembly

(purchased separately) installed in the tbus, as follows:

Universal: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet

USA: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet

Germany and EU: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet

Belgium and France: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet

Italy: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet

Australia: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet

Israel: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet

South Africa: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet

Switzerland: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet

England: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet

Brazil: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet

Fuse Rating: T 6.3A 250V

Accessories Included: Mounting brackets

Optional: TBUS AC Power Cord, power socket kits

Product Dimensions 15.70cm x 12.80cm x 15.35cm (6.18" x 5.04" x 6.04") W, D, H

Product Weight 0.9kg (1.9lbs) approx

Shipping Dimensions 36.50cm x 17.00cm x 17.00cm (14.37" x 6.69" x 6.69") W, D, H

Shipping Weight 1.2kg (2.6lbs) approx

