

## **RTBUS-27xl**

Round Table Connection Bus for Power Socket and Cable Pass-Throughs



RTBUS 27xl is an elegant furniture-mounted, round connection bus that houses a power socket and two cable pass-throughs. RTBUS 27xl features a pneumatic lid mechanism for lifting and smooth closing and is easily installed into a table or podium top.

NOTE: The power socket, power cord and cables are purchased separately

## FEATURES

Customizable - Houses any of the following power sockets: USA, UK, Germany (the Europlug), Belgium-France, Switzerland, Italy, Australia, Brazil, Israel, South Africa or "Universal" for use anywhere

Hidden Cable Pass-Throughs - Enable closing the lid while keeping two cables hidden and protected under the table surface

Cutout Size (Mount Dimension) - 111-114mm (4.37in to 4.49in) diameter



## TECHNICAL SPECIFICATIONS

| Extended USB  | Cutout Size 111–114mm (4.37in to 4.49in) diameter   |
|---|---|
| Power   | Power rating varies according to the location and the power socket assembly (purchased separately) installed in the tbus, as follows: |
|   | Universal: 100–240V AC, 50/60Hz, 5A, maximum 5A per power outlet  |
|   | USA: 100–240V AC, 50/60Hz, 5A, maximum 5A per power outlet  |
|   | Germany and EU: 100–240V AC, 50/60Hz, 5A, maximum 5A per power outlet   |
|   | Belgium and France: 100–240V AC, 50/60Hz, 5A, maximum 5A per power outlet   |
|   | Italy: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet  |
|   | Australia: 100–240V AC, 50/60Hz, 5A, maximum 5A per power outlet  |
|   | Israel: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet   |
|   | South Africa: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet   |
|   | Switzerland: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet  |
|   | England: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet  |
|   | Brazil: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet   |
|   | Fuse Rating: T 6.3A 250V  |
| Environmental<br>Conditions                           | Operating Temperature: 0° to +40°C (32° to 104°F)   |
|   | Storage Temperature: -40° to +70°C (-40° to 158°F)  |
|   | Humidity: 10% to 90%, RHL non-condensing  |
| Regulatory<br>Compliance<br>(Standards<br>Compliance) | Safety: CE, UL  |
|   | Environmental: RoHs, WEEE   |
| COAX  | Included Clamp set  |
| Optional  | TBUS AC Power Cord, power socket kits   |



| CONFIGURATIONS |  |
|----------------|--|
| RTBUS-27XL(B)  | Round Table Connection Bus — Sand-blasted Anodized Aluminum Top - Black  |
| RTBUS-27XL(BC) | Round Table Connection Bus — Sand-blasted Anodized Aluminum Top - Silver |