



kramer

RTBUS-28XL

Round Table Connection Bus for Power Socket , USB Charging and Cable Pass-Throughs



The RTBUS-28XL is an elegant furniture-mounted, round-connection bus. The RTBUS-28XL features a mechanism for pneumatic lifting and smooth closing of its lid. It is easily installed into a table or podium top. In addition, the unit connects AV equipment to the room's presentation system

TECHNICAL SPECIFICATIONS

Ports	USB-C: On a USB-C port (fast charge) USB Type A: On a USB port (fast charge)
USB Features	Rated USB Output: DC 5 V Protocol Type-A: QC 3.0 Protocol Type-C: PD 5 Output Power: 30W max Output Current Voltage Type-A: 5V=3A, 9V=3A, 12V=2.5A, 20V=1.5A Output Current Voltage Type-C: 5V=3A, 9V=3A, 12V=2.5A, 15V=2A, 20V=1.5A Note: Some laptops may require more than 30W power for charging. Additionally, when connecting USB-A in parallel, the USB-C port may not support laptop charging Output Current Voltage Type-A & Type-C: 5V=2.4A
Power	Power Socket - Universal: 100-240V AC, 50/60Hz, 5A; maximum 5A per power outlet Fuse Rating: T 6.3A 250V Options: TBUS AC Power Cord (C-AC/POWERCORD) power socket kits Note: When using an IL plug, it is necessary to use straight configurations cable
Regulatory Compliance (Standards Compliance)	Safety: CE Environmental: RoHS, WEEE
Environmental Conditions	Operating Temperature: 0° to +40°C (32° to 104°F) Storage Temperature: -40° to +70°C (-40° to 158°F) Humidity: 10% to 90%, RHL non-condensing
General	Product Dimensions (Diameter, H): 15.5cm x 14.6cm (6.1" x 5.7")

Shipping Dimensions: 27.5cm x 22cm x 19.5cm (10.8" x 8.7" x 7.7") (W, D, H)

Product Weight: 1.32kg (2.9lbs) approx

Shipping Weight: 1.9kg (4.2lbs) approx



kramer

CONFIGURATIONS

RTBUS-28XL(B) Round Table Connection Bus for Power Socket , USB Charging and Cable Pass-Throughs

RTBUS-28XL(BC) Round Table Connection Bus for Power Socket , USB Charging and Cable Pass-Throughs

