TSD-TXHL



High/Low Level Converter





TSD-TXHL

Features

- Speaker Level to Line Level Conversion
- Works with $4\Omega/25/70/100V$ Speaker Systems
- Variable Output Level
- Transformer Isolated
- Trim Level Control
- Cable Management System
- Multiple Mounting Configurations
- Wide Bandwidth Frequency Response
- Separate Ground Connections
- Removable I/O Connectors
- No External Power Required
- Compact Chassis Design

Audio Applications

- System Isolation
- Level Matching
- Add a Zone Anywhere a Speaker System Exists

Atlas Time Saving Devices

New Atlas Sound Time Saving Devices are designed to solve some of the common audio system problems in the easiest and in the most efficient and cost-effective way. Utilizing the highest quality components and inspired by real world installation issues, the Atlas Sound TSDs include mixers, amplifiers, preamps, and other distribution and control devices to simplify your connections, provide specific application needs, and add flexibility in expansion and changes that prevent expensive system overhauls.

The Time Saving Devices are loaded with features making it versatile and user friendly. The TSD design mandate was to make the installation quick and reliable, saving you valuable time and money. Each model is housed in a compact 1.5" x 4" x 2.75" footprint that allows for placement almost anywhere. Common features include removable individual I/O connectors for quick and precise wiring, separate ground terminals for all I/Os assuring secured connections, and removable level controls that can be replaced with a tamper-proof security cover.

Description

The Atlas Sound TSD-TXHL is a high to low level converter designed to interface with $4\Omega/25/70/100V$ distributed speaker lines. An unbalanced line level output is provided to drive remote amplifiers or other devices. The TSD-TXHL allows easy expansion of zones without the need for dedicated wiring to remote locations. The high to low-level converter features an isolated transformer, which will not add measurable load to the speaker line. An output level control allows for trim adjustment to best match the remote amplifier (or other device) input sensitivity. The TSD-TXHL works perfectly in conjunction with Atlas Sound's CP and PA series.

Installation

- Government Buildings
- Medical Facilities
- Office Environments
- Churches
- Restaurants
- Schools
- Industrial Facilities
- House of Worship



Specifications

Description High Level to Line Level Convertor and Signal Isolator

Chassis ColorBlackChassis MaterialAluminum

Inputs

High Level Input Oty 1, Amplifier Speaker Outputs 4Ω , 8Ω , 25V, 70V, 100V Connection Removable 2 Position Captive Screw 3.5mm Spacing

Outputs

Type Qty 1, Unbalanced Line

Connection Removable 2 Position Captive Screw 3.5mm Spacing

 $\begin{array}{ll} \text{Impedance} & 600\Omega \text{ Unbalanced} \\ \text{Line Output Level} & \text{Max Output 1V } \pm 10\% \end{array}$

Controls

Input Level Adjustment Three Selections 4Ω -25V, 70V, 100V

Electrical

Transformer Isolation Step Down Frequency Response 40Hz - 25kHz (-3dB)

Mounting

Velcro Industrial Grade, Included

Brackets Oty 2, Included

TSD-RMK Optional 1 RU Rack Mount Panel (Supports 4 TSD Units)

Power Requirements

None Passive

Dimensions H 1.5" (39mm) x W 4" (101mm) x D 2.75" (70mm)

Weight 6oz, .165kg





