



## VP-427X2

4K HDR HDBT Receiver / Scaler Tool with  
HDBaseT and HDMI Inputs

| HDMI | Ethernet - RJ-45



VP-427X2 is a high-performance auto-switcher/scaler receiver with 2 HDBaseT inputs and a local HDMI input for 4K HDMI™ over extended-reach HDBaseT. It supports automatic and manual glitch-free switching between the 3 inputs, and up- or down-scaling to any resolution up to 4K@60Hz (4:4:4). The output scaling automatically matches the resolution of the HDMI display on the output, or it can be manually set by the user. VP-427X2 enables extending video signals up to 180m over CAT copper cables at up to 4K@60Hz (4:2:0) 24bpp video resolution and provides even further reach for lower HD video resolutions

### FEATURES

**Comprehensive Receiver/Scaler** - Scales signals of all standard resolutions up to 4K@60Hz (4:4:4) for routing to the HDMI output. Constant output sync prevents signal disruption when switching between inputs and when no video is detected

**HDMI Signal Extension** - HDCP 1.4 / 2.2. 4K60, CEC, xvYCC color (on input)

**Audio De-embedding** - Analog balanced stereo output for de-embedding the audio to speakers

**Data Tunneling** - Extend RS-232, IR, and Ethernet over the HDBaseT line

**Built-in Automated Control** - Includes relay outputs and easy connection to occupancy sensors and contact closure switches

**CEC Support** - Supports passing of CEC from input to output. Automatically sends CEC commands to shut down the output display after a timeout period when no input signal is found and to power up the display when the input returns

**Cost-Effective and Convenient Control Options** - Ethernet and RS-232 serial ports, and local control via front panel input selection and OSD menu buttons

**ProcAmp Control** - Contrast, brightness, color, etc

**Convenient Unit Control and Configuration Options** - Local control via front panel source switching buttons and OSD menu. Distance control via RS-232 serial commands transmitted by a PC, touch screen system or other serial controller and relay switches

**Easy, Cost-effective Maintenance** - Local firmware upgrade via USB connector

**Easy and Elegant Installation** - Compact MegaTOOLS™ fan-less enclosure for dropped-ceiling mounting, or side-by-side mounting of 2 units in a 1U rack space with the recommended rack adapter



## TECHNICAL SPECIFICATIONS

---

Inputs	2 HDBaseT: On an RJ-45 connector 1 HDMI: On a female HDMI connector
Outputs	1 HDMI: On a female HDMI connector 1 Balanced Analog Stereo Audio: On a 5-pin terminal block
Ports	1 IR: On a 3.5mm mini jack 1 RS-232: On a 3-pin terminal block 1 Ethernet: On an RJ-45 connector
Video	Output Resolutions: 640x480@60Hz, 800x600@60Hz, 1024x768@60Hz, 1280x768@60Hz, 1280x800@60Hz, 1280x1024@60Hz, 1360x768@60Hz, 1400x1050@60Hz, 1440x900@60Hz, 1600x1200@60Hz, 1680x1050@60Hz, 1920x1200@60Hz RB, 2560x1600@60Hz RB, 1920x1080@60Hz, 1280x720@60Hz, 2048x1080@50/60Hz, 2560x1440@60Hz RB, 720x480p@60Hz, 720x576p@50Hz, 1280x720p@50/60Hz, 1920x1080p@24/25/30/50/60Hz, 2560x1080p@50/60Hz, 2K@24/25/30/50/60Hz, 4K@24/25/30/50/60Hz Max. Range: 180m at 1080p@60Hz, 100m (328ft) at 4K@60Hz (4:2:0) Latency: Up to 2 frames Content Protection: HDCP 2.2/1.4 Switching Time Between Inputs: <2.5 seconds
User Interface	Control: Input selection buttons, remote contact-closure switches, relay switches. Kramer API via RS-232 serial commands transmitted by a PC, touch screen system or other serial controller, embedded web pages via LAN for configuration and control Indicators: Power, link, input selection LEDs
Power	Source: 12V DC Consumption: 2.1A
Enclosure	Size: MegaTOOLS® Type: Aluminum Cooling: Convection ventilation
Environmental Conditions	Operating Temperature: 0° to +40°C (32° to 104°F) Storage Temperature: -40° to +70°C (-40° to 158°F) Humidity: 10% to 90%, RHL non-condensing
Accessories	Included: Power adapter, rubber feet, mounting bracket
Product Dimensions	18.75cm x 14.50cm x 2.54cm (7.38" x 5.71" x 1.00" ) W, D, H
Product Weight	1.1kg (2.4lbs) approx
Shipping Dimensions	35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83" ) W, D, H
Shipping Weight	1.7kg (3.8lbs) approx



