



# kramer

## MC3-2HAo

4K60 HDMI 2xOUT Card with Analog Audio

| HDMI | 4K/60 UHD (4:4:4)



MC3-2HAo is a high-performance two-port HDMI input card which is part of the compatible modular matrices multi-signal cards family. MC3-2HAo can flexibly occupy any of the matrix card slots and its output signals are independently switched by the modular matrix to any of the matrix output ports. The card dual analog audio ports enable, independently per port, audio de-embedding or embedding

### FEATURES

**High Resolution Audio-Visual Experience** - Modular matrix output card supports high 4K60 4:4:4 AV signal distribution from any input port of the modular matrix

**HDMI™ Signal Distribution** - HDCP 2.2 compliant, supporting deep color, x.v.Color™, CEC, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D as specified by the HDMI 2.0 standard

**Multi-channel Audio Transmission** - Up to 32 channels of digital stereo uncompressed signals for supporting studio-grade surround sound

**Intelligent Forward Audio Routing** - Per user selection, independently per port, an analog audio port input signal is converted into a digital signal and embedded into the output HDMI signal, or the embedded HDMI audio output signal is de-embedded and output to the analog audio port. This enables temporarily overriding the audio with another audio source, or playing the audio output on high-quality external speakers

**Intelligent ARC (Audio Return Channel) Routing** - The output-returned ARC signal, per user selection, independently per port, is routed to the analog audio bidirectional port that is associated with the HDMI output port. This enables playing the ARC audio on high-quality external speakers, and controlling its volume using an IR remote control either via a remote AV acceptor device (such as a display) or via a local AV acceptor device (such as an AV Receiver with speakers)



# kramer

## TECHNICAL SPECIFICATIONS

---

|  |   |
|--|---|
| Outputs                                      | 2 HDMI: On female HDMI connectors   |
| Ports  | 2 Unbalanced Analog Audio: on 3.5mm mini jacks  |
| Video  | Max Data Rate: 18Gbps (6Gbps per graphics channel)<br><br>Max Resolution: 4K@60Hz (4:4:4)<br><br>HDMI Support: HDR 10, 3D, Deep Color, x.v.Color™, ARC, Dolby® TrueHD, Dolby Digital Plus, DTS-HD®, and 7.1 multi-channel audio |
| User Interface                               | Content Protection: HDCP 2.2/1.4 compliant  |
| Power  | Consumption 5W  |
| Regulatory Compliance (Standards Compliance) | Safety CE   |
| Environmental Conditions                     | Operating Temperature: 0° to +40°C (32° to 104°F)<br><br>Storage Temperature: -40° to +70°C (-40° to 158°F)<br><br>Humidity: 10% to 90%, RHL non-condensing   |
| Product Dimensions                           | 12.90cm x 24.90cm x 2.00cm (5.08" x 9.80" x 0.79" ) W, D, H   |
| Product Weight                               | 0.1kg (0.3lbs) approx   |
| Shipping Dimensions                          | 16.50cm x 34.50cm x 5.90cm (6.50" x 13.58" x 2.32" ) W, D, H  |
| Shipping Weight                              | 0.4kg (0.9lbs) approx   |

