

PT-110xI

Computer Graphics Video over Twisted Pair Transmitter with EDID





The PT-110xl is an extended range UXGA line transmitter that receives a UXGA signal and transmits it over a CAT 5/6 cable to the PT-120xl or TP-120 receiver

FEATURES

Resolution - Up to WUXGA & 1080p

HDTV Compatible

Power Connect™ System - A single connection to the transmitter or the receiver powers both units when the devices are within 150ft (50m) of each other

Extended Transmission Range - Up to 250m (820ft) when used with Kramer's twisted pair xl receivers (such as PT-120xl, TP-122xl or TP-126xl)

EDID Capture - Copies and stores the EDID from a display device

Increased Noise Immunity - An increased level of protection against noise, spikes and interference in adverse environments



TECHNICAL SPECIFICATIONS

INPUT: 1 VGA/UXGA on a 15-pin HD connector

OUTPUT: 1 twisted pair on an RJ-45 connector

RESOLUTION: Up to WUXGA, 1080p

RANGE: Up to 250m (820ft)

S/N RATIO: Paired with PT-120xI, better than 70dB (worst case)

COUPLING: AC

POWER 12V DC, 285mA

CONSUMPTION:

OPERATING 0° to $+40^{\circ}$ C (32° to 104° F)

TEMPERATURE:

STORAGE -40° to $+70^{\circ}$ C (-40° to 158° F)

TEMPERATURE:

HUMIDITY: 10% to 90%, RHL non-condensing

INCLUDED Power supply

ACCESSORIES:

Product Dimensions 6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96") W, D, H

Product Weight 0.1kg (0.2lbs) approx

Shipping Dimensions $17.40 \text{cm x} \ 12.00 \text{cm x} \ 8.60 \text{cm} \ (6.85\text{" x} \ 4.72\text{" x} \ 3.39\text{"}) \ \text{W, D, H}$

Shipping Weight 0.5kg (1.1lbs) approx

