⟨i⟩ infobit



iTrans DU-TR-22C

Dante USB I/O
Transceiver

All Rights Reserved

Version: V1.0

Product Introduction

Thanks for choosing the iTrans DU-TR-22C. It connects to your Dante network and supports 2X2 channels of bidirectional audio, allowing PC and mobile device to playout and receive audio with your Dante devices using a USB-A/C connection.

Features

- Plug and Play
- 24-bit audio support
- 2X2 audio channel
- Supports 802.3af PoE

Packing List

- 1 x iTrans DU-TR-22C
- 1 x Type-C to Type-C cable
- 1 x Type-C to Type-A cable
- 1 x User Manual

Note: Please contact your distributor immediately if any damage or defect in the

components is found

Panel Description



- RJ45: Dante network communication port. Green steady light indicates system ready; yellow flashing light indicates link/data traffic. The green light will flash to identify the device when clicking the Dante Controller "Identify" button (an eye-shaped symbol) on the host computer.
- ② USB-C: 1 x USB-C, compliant USB 2.0 device

⟨i⟩ infobit

Technical Specification

Dante	
Power	802.3af PoE
Sample Rate	48 kHz
Bit Depth	24
Channels	USB 2X2
General	
Operation	-5 to +55℃
Temperature	
Storage	-25 to +70°C
Temperature	
Power	9W(Max)
Consumption	
Dimension	115x 34 x 28
(W*H*D)	mm
Cable length	20cm
Net Weight	70q







WWW. INFOBITAV. COM INFO@INFOBITAV. COM