

Models compare	E70C	E150CL	E150CG
Distance	1080P/60Hz 70m; 4K/30Hz 40m	1080P/60Hz 150m	1080P/60Hz 150m; 4K/60Hz 120m
Must be used in pair	No, Tx/Rx can be used separately	Yes	Yes
Loopout	No	Yes	Yes
De-embedded audio	No	No	Yes
HDR	No	No	Yes
HDMI	HDMI 1.4, 10.2Gpbs	HDMI 1.4, 10.2Gpbs	HDMI 2.0b, 18Gpbs
HDCP	HDCP 2.2	HDCP 1.4	HDCP 1.4/ 2.2
POC (Power Over Cable)	Yes	Yes	Yes
Bi-directional IR and RS232	Yes	Yes	Yes
Transmitter I/O	Input: 1xHDMI Type A, 19-pin Output: 1xHDBaseT Out, RJ45 Control: 1xIR In (3.5mm Stereo Mini-jack); 1xIR Out (3.5mm Stereo Mini-jack); 1xRS-232 (Phoenix jack)	Input: 1x HDMI Type A, 19-pin female Output: 1x HDBaseT Out, RJ45; 1x HDMI Type A, 19-pin female (loopout); Control: 1x IR In (3.5mm Stereo Mini-jack); 1x IR Out (3.5mm Stereo Mini-jack); 1x RS232 (Phoenix jack)	Inputs: 1x HDMI Type A, 19-pin female; 1x SERVICE (Mini-USB, Update port) Outputs: 1x HDBaseT OUT, RJ45; 1x HDMI Type A, 19-pin female (loopout); Control: 1x IR In (3.5mm Stereo Mini-jack); 1x IR Out (3.5mm Stereo Mini-jack); 1x RS-232 (Phoenix jack)
Receiver I/O	Input: 1x HDBaseT Input, RJ45 Output: 1x HDMI Type A, 19-pin Control: 1xIR In (3.5mm Stereo Mini-jack); 1xIR Out (3.5mm Stereo Mini-jack); 1xRS-232 (Phoenix jack)	Input: 1x HDBaseT Input, RJ45 Output: 1x HDMI Type A [19-pin female] Control: 1x IR INPUT (3.5mm Stereo Mini-jack); 1x IR Out (3.5mm Stereo Mini-jack); 1x RS232 (Phoenix jack)	Inputs: 1x HDBaseT Input, RJ45; 1x SERVICE (Mini-USB, Update port) Outputs: 1x HDMI Type A, 19-pin female; 1x AUDIO OUT (3.5mm Stereo Mini-jack); Control: 1x IR IN (3.5mm Stereo Mini-jack); 1x IR Out (3.5mm Stereo Mini-jack) 1x RS-232 (Phoenix jack)
Net Dimensions	WHD: 120mm x 16mm x 74mm	WHD: 140mm x 18mm x 65mm	WHD: 140mm x 18mm x 65mm
Net Weight	240g/ Tx or Rx	240g/ Tx or Rx	Tx: 160g, Rx: 155g
Power Supply	Input: AC100 - 240V 50/60Hz Output: DC 24V/1A (US/EU standards, CE/FCC/UL certified)	Input: AC100 - 240V 50/60Hz Output: DC 24V/1A (US/EU standards, CE/FCC/UL certified)	Input: AC100 - 240V 50/60Hz Output: DC 24V/1A (US/EU standards, CE/FCC/UL certified)
Power Consumption	10W	6W	9.36W
Operation Temperature	32 - 104°F / 0 - 40°C	32 - 104°F / 0 - 40°C	32 - 104°F / 0 - 40°C
Storage Temperature	-4 - 140°F / -20 - 60°C	-4 - 140°F / -20 - 60°C	-4 - 140°F / -20 - 60°C
Relative Humidity	20 - 90% RH (non condensation)	20 - 90% RH (non condensation)	20 - 90% RH (non condensation)