

Models Compare	WP70-T	WP210-T	WP200-Kit
Type	1-Gang US Decora	2-Gang US Decora	1x WP200T Wall Plate ( US 2-Gang) Tx; 1x WP200R receiver, 1x WP200C control panel
Distance	4K60Hz 4:4:4 40m/130ft; 1080p 70m/230ft	4K60Hz 4:4:4 40m/130ft; 1080p 70m/230ft	4K30Hz 4:4:4 40m/130ft; 1080p 70m/230ft
HDMI	HDMI 2.0b, 18 Gbps	HDMI 2.0b, 18 Gbps	HDMI 1.4b, 10.2 Gbps
HDCP	HDCP 1.4 and HDCP 2.2	HDCP 1.4 and HDCP 2.2	HDCP 1.4 and HDCP 2.2
POC (Power Over Cable)	Yes	Yes	Yes
Bi-directional IR and RS232	Yes	Yes	Yes
HDMI Video Resolution	4K/60Hz (YUV4:4:4), 4K/30Hz, 1080P/120Hz, and 1080P 3D/60Hz	4K/60Hz (YUV4:4:4), 4K/30Hz, 1080P/120Hz, and 1080P 3D/60Hz	4K30Hz, 1080p
VGA resolution	No VGA	1080p/60Hz, with scalling	1080p/60Hz, with scalling
Control panel	Without	Without	Yes
Web GUI control	No	No	Yes
Whiteboard Touch	No	No	Yes
HDMI Audio Formats	LPCM 2/5.1/7.1CH, Dolby Digital, DTS 5.1, Dolby Digital+, Dolby TrueHD, DTS-HD Master Audio, Dolby Atmos, DTS:X	LPCM, Dolby Digital/Plus/EX, Dolby True HD, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD Master Audio, DSD	LPCM 2/5.1/7.1CH, Dolby Digital, DTS 5.1, Dolby Digital+, Dolby TrueHD, DTS-HD, Dolby, DTS
Transmitter I/O	Inputs: 1x HDMI Type A, 19-pin female; 1x IR INPUT, Phoenix jack; 1x RS-232, Phoenix jack; Outputs: 1x HDBaseT Out, RJ45; 1x IR OUT, Phoenix jack; 1x RS-232, Phoenix jack;	Inputs: 1x HDMI Type A, 19-pin female; 1x VGA; 1x USB-B; 1x IR IN, Phoenix jack; 1x RS-232, Phoenix jack; 1xAUDIO IN, 3.5mm Stereo Mini-jack. Outputs: 1x HDBaseT Out, RJ45; 1x IR OUT, Phoenix jack;	Inputs: 2x HDMI IN Type A, 19-pin female; 1x VGA, DB15 VGA female; 1x AUDIO IN, 3.5mm Stereo Mini-jack; 1x RS-232/POWER, RJ45; Outputs: 1x HDBaseT Out, RJ45
Receiver I/O	Receiver not included, infobit HDBaseT extender can be purchased separately.	Receiver not included, infobit HDBaseT extender can be purchased separately.	Inputs: 1x 3PIN MIC/line; 1x USB-A; 1x TCP/IP; 1x USB-A; 1x HDBaseT, RJ45; Outputs: 1x HDMI OUT Type A, 19-pin female; 1x RS-232; 1x RELAY, Screw Terminal; 1x 2x30watts/4 ohms amplifier output
Net Dimensions	WHD: 103.5mm x 30mm x 46mm	WHD: 91.8mm x 43mm x 104.8mm	Transmitter: WHD 115.9mm x 38.7mm x 114.3mm Receiver: WHD 250mm x 30mm x 104mm Control Panel: WHD 69.9mm x 22.2mm x 114.3mm
Net Weight	163g	212.5g	Transmitter: 305g; Receiver: 790g; Control Panel: 180g
Power Supply	Input: AC100 - 240V 50/60Hz Output: DC 24V/1A (US/EU standards, CE/FCC/UL certified)	Input: AC100 - 240V 50/60Hz Output: DC 24V/1A (US/EU standards, CE/FCC/UL certified)	Input: AC100 - 240V 50/60Hz Output: DC 24V/1A (US/EU standards, CE/FCC/UL certified)
Power Consumption	9W	6W	75W
Operation Temperature	32 - 104°F / 0 - 40°C	32 - 104°F / 0 - 40°C	32 - 104°F / 0 - 40°C
Storage Temperature	-4 - 140°F / -20 - 60°C	-4 - 140°F / -20 - 60°C	-4 - 140°F / -20 - 60°C
Relative Humidity	20 - 90% RH (non condensation)	20 - 90% RH (non condensation)	20 - 90% RH (non condensation)